



No Hassle Compression

CC100 - 100 HP

DISCHARGE PRESSURE (psig)

SUCTION	DISCHARGE PRESSURE (psig)										
	60	80	100	120	140	160	180	200	220	240	250
5	800	795	690	680	675	555	550	530	495	480	475
10	1020	1015	880	715	705	700	695	590	545	525	520
20		1060	1050	885	875	735	720	720	685	625	620
30		1040	1040	1040	990	975	825	810	745	735	710
40			1180	1180	1180	1025	1015	825	810	760	720
50				1230	1230	1230	1215	975	965	950	900
60					1140	1140	1140	1115	1100	1080	1060
70						1300	1300	1300	1280	1250	1230

• Pressures in PSI • Flow Rates in MSCFD

*Performance based on 2500 ft, gas density .665, temp 68 °F using Enduro G-2 V2 Selector Program

CC100

Standard Features

Compressor – Gardner Denver Enduro 25

Driver – Cummins G8.3

Weight – 9,000lb / 4,080kg

Compressor Speed Optimization

Options

- Easy 1 Controller
- Sound Proofing
- SCADA Output
- Blowcase
- Fire & Gas Detection



Phone: (403) 219-3026
Fax: (403) 717-1759

#8, 1820 - 30th Ave. NE
Calgary, Alberta Canada T2E 7M5

info@compactcompression.com