



No Hassle Compression

CC50 - 50 HP

SUCTION	DISCHARGE PRESSURE (psig)										HIGH PRESSURE OPTION		
	60	80	100	120	140	160	180	200	220	240	260	280	300
2	354	349	307	303	257	253	248	206	194	185	177		
5	420	415	365	360	305	300	295	245	230	220	210	200	190
10	525	460	390	388	385	325	323	320	300	235	225	215	210
20		650	560	475	470	390	385	380	375	285	275	265	250
30		720	720	620	520	510	425	420	415	320	305	290	280
40			765	765	650	540	525	515	425	410	390	375	360
50				905	770	625	620	520	515	505	415	400	390
60					900	750	730	605	590	495	490	480	465
70						860	715	705	690	575	560	545	530

• Pressures in PSI • Flow Rates in MSCFD

*Performance based on 2500 ft, gas density .665, temp 68 °F using Enduro G-2 V2 Selector Program

CC50

Standard Features

Compressor – Gardner Denver Enduro 12

Driver – Teco 5700

Weight – 5,500lb / 2,500kg

Compressor Speed Optimization

Options

- Easy 1 Controller
- Sound Proofing
- SCADA Output
- Blowcase
- Fire & Gas Detection



Phone: (403) 219-3026
Fax: (403) 717-1759

#8, 1820 - 30th Ave. NE
Calgary, Alberta Canada T2E 7M5

info@compactcompression.com